

SafetyPro™ JR Label Printer

DETAILED PRINTER SPECIFICATIONS



Software Specifications

Bundled Software	Labeling Software Windows Drivers
Bundled Images	900+ OSHA, ANSI and general safety pictograms in WMF (vector) format
Supported Barcodes	Code 39/E, Code 93, Code 128 UCC/ABC, CodeBar, 2 of 5, EAN-8 2&5, EAN-13, EAN-128, UPC, UPC-A, POSTNET, Matrix 25



11918 SE Division St. #109
Portland OR 97266
Toll Free: (877) 762-9280
Fax: (503) 761-2838
www.industrialsafetysolution.com

Print Specifications

Print Quality	High-Def 128µm
Print Speed	Up to 4"/sec
Media Width	1" – 4.1"
Media Length	150' (1800")

Physical Specifications

Physical Dimensions	10" x 8" x 6.5" (L x W x H)
Max. Material Size	5" OD
Weight	5.0 lbs (Unloaded)

System Specifications

Computer Interface	USB Parallel Serial
Processor	32-bit RISC CPU
Memory	2MB Flash 2MB DRAM

Service Specifications

Power	AC Input: 100V-240V Universal Switching DC Output: 24V @ 3.75A
Storage Temperature Service Temperature	-40F - 140F 41F - 104F

The SafetyPro conforms to the following International Safety Specifications:

CE | UL | CUL | FCC Class A | CCC

The SafetyPro JR Labeling System is a desktop class label and sign printer. This unit was engineered for durability and long print life. Under heavy use, the print-head components should last at least 1 million inches. Industrial Safety Solutions offers certified repair, reconditioning and replacement services should your label printer need attention.

Toll Free Tech Support: (877) 762-9280 - www.industrialsafetysolution.com

Copyright 2007, Industrial Safety Solutions - Document Version 1.02